



PRODUCT SPECIFICATION

LPT-A-CH2O Transmitter

Analog Transmitter with Formaldehyde sensor (CH₂O)

	Standard Enclosure
Dimensions: Size Weight	5.0" X 5.0" X 2.4" (127 mm x 127 mm x 60.96 mm) (dimensions with optional splash guard) 14 ounces (400 g)
Construction	ABS / Polycarbonate blend, water/dust tight, corrosion resistant (designed to meet IP54 standard)
Sensors: Type Life Span	Electrochemical Approximately 2+ years in normal operation
Gases Detected	Calibrated for CH ₂ O
Sensor Range	0 – 10 ppm standard.
System Power	3-wire: VDC: 12-30 VDC, 3-Watts 4-wire: VAC: 12-27VAC, 3-VA
Temperature	-20°C to +50°C (-4°F to 122°F), -40°C (-40°F) with LCD heater option
Humidity	15 to 90% non-condensing
Indicators	LCD digital display, back lit, 128 X 64 pixel graphic
Signal	Current: Linear 4-20 mA (maximum 216 ohm load, wiring plus termination resistor @ 12VDC) Maximum 316 ohm load, wiring plus termination resistor @ 12VAC Voltage: 0-10 Volt, Minimum 1k ohm load
Minimum Detection	0.1 ppm (with regular calibration maintenance of sensor)
Repeatability	< 2% (with regular calibration maintenance of sensor)
Accuracy	+/- 5% of range @ STP (with regular calibration maintenance of sensor)
Response time	<40 seconds T ₆₀
Resolution	0.01 ppm
Warm Up Time	3-minutes after power up (to 80% of range). Warm up time dependent upon how long sensor has been without power. Long periods may require a 6+ hour warm up to meet published specification
Cross Sensitivity	Carbon Monoxide (CO) 10%-18%, Hydrogen (H ₂) 1%-3%
Fusing	Automatic resetting thermal overload fuse (reset capabilities to 500 times)
Wiring	VDC or ground referenced VAC, 3-conductor shielded 18 awg stranded VAC 4-conductor shielded 18 awg stranded
Sensor Mounting	Slightly heavier than air
Monitoring Area	3000 sq. ft. (application dependent)
Certifications	CSA: C22.2 NO.205-M1983 (R2009) UL: UL508 (Edition 17): 2007 CE: EMC-EN50270:2006, Type-1 & EN61000-4-2 to 11 FCC
Note	Never install gas detectors in the direct path of moving air.

Rev: 1-6-17